Docket No. AUS990940US1

HYPERVISOR AS A SET OF SERVICES

BACKGROUND OF THE INVENTION

Cross Reference to Related Applications

The present application is related to co-pending U.S. Patent Application Serial No. _____ (IBM Docket No. AUS990939US1) entitled "HYPERVISOR FUNCTION SETS" filed _____. The content of the above-mentioned commonly assigned, co-pending U. S. Patent application is hereby incorporated herein by reference for all purposes.

1. Technical Field:

The present invention relates generally to the field of computer architecture and, more specifically, to methods and systems for managing resources among multiple operating system images within a logically partitioned data processing system.

2. Description of Related Art:

A logical partitioning option (LPAR) within a data processing system (platform) allows multiple copies of a single operating system (OS) or multiple heterogeneous operating systems to be simultaneously run on a single data processing system platform. A partition, within which an operating system image runs, is assigned a non-overlapping subset of the platform's resources. These platform allocable resources include one or more architecturally distinct processors with their interrupt

management area, regions of system memory, and I/O adapter bus slots. The partition's resources are represented by its own open firmware device tree to the OS image.

Each distinct OS or image of an OS running within the platform are protected from each other, such that software errors on one logical partition cannot affect the correct operation of any of the other partitions. This is provided by allocating a disjoint set of platform resources to be directly managed by each OS image and by providing mechanisms for ensuring that the various images can not control any resources that have not been allocated to it. Furthermore, software errors in the control of an OS's allocated resources are prevented from affecting the resources of any other image. Thus, each image of the OS (or each different OS) directly controls a distinct set of allocable resources within the platform.

A significant problem with logically partitioned platform has been "when" to run trusted platform firmware to create and enforce the partitioning of the platform's resources. In general, there have been two answers. One solution is to run the firmware prior to starting the OS image, at which time special hardware is set up to restrict the access that the OS image can make. The other solution is to run the firmware when certain privileged instructions that may change the environment are trapped (i.e. prevented from executing). Both of these answers have drawbacks. The special hardware solution results in overly constraining the OS image to run in a fixed set of resources that can be managed by

the hardware. The trapping on privileged instruction solution tends to create a significant performance penalty since most of the time the trapped instructions were being used for other purposes than to change the OS image's environment. Therefore, a method of creating and enforcing the partitioning of a platform's resources that allows for the significant flexibility in the assignment of resources of the instruction trap approach, and that also maintains a level of performance more closely associated with the hardware approaches is desirable.

SUMMARY OF THE INVENTION

The present invention provides a method, apparatus, and system for preventing each of a plurality of operating system within a logically partitioned data processing system from interfering with the operation of the other operating systems. In one embodiment, a logically partitioned data processing system includes a plurality of logical partitions; a plurality of operating systems, a plurality of assignable resources, at least one non-assignable resource, and a hypervisor. Each of the plurality of operating systems is assigned to a separate one of the plurality of logical partitions and each of the plurality of assignable resources is assigned to one of the plurality of logical partitions. The hypervisor provides a set of services to each of the plurality of logical partitions, wherein these services safely perform modifications to non-assignable processing system resources in response to operating system requests without allowing direct access to the non-assignable resources by the operating system image. Thus, each operating system is prevented from modifying the non-assignable resource in such a way that interferes with the operation of other ones of the plurality of operating systems.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as, a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts a pictorial representation of a distributed data processing system in which the present invention may be implemented;

Figure 2, a block diagram of a data processing system in accordance with the present invention is illustrated;

Figure 3 depicts a block diagram of a data processing system, which may be implemented as a logically partitioned server, in accordance with the present invention;

Figure 4 depicts a block diagram of a logically partitioned platform in which the present invention may be implemented;

Figure 5 depicts a flowchart illustrating an exemplary process for preventing each of multiple OS images within a logically partitioned platform from interfering with other OS images in accordance with the present invention; and

Figure 6 depicts a high level flowchart illustrating an exemplary process within an operating system image for requesting operations to a logically partitioned platform

in accordance with the present invention.

D0E0D0E0D0E0

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular with reference to **Figure 1**, a pictorial representation of a distributed data processing system is depicted in which the present invention may be implemented.

Distributed data processing system **100** is a network of computers in which the present invention may be implemented. Distributed data processing system **100** contains network **102**, which is the medium used to provide communications links between various devices and computers connected within distributed data processing system **100**. Network **102** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections.

In the depicted example, server **104** is connected to hardware system console **150**. Server **104** is also connected to network **102**, along with storage unit **106**. In addition, clients **108**, **110** and **112** are also connected to network **102**. These clients, **108**, **110** and **112**, may be, for example, personal computers or network computers. For purposes of this application, a network computer is any computer coupled to a network that receives a program or other application from another computer coupled to the network. In the depicted example, server **104** is a logically partitioned platform and provides data, such as boot files, operating system images and applications, to clients **108-112**. Hardware system console **150** may be a laptop computer and is used to display messages to an

operator from each operating system image running on server **104**, as well as to send input information, received from the operator, to server **104**. Clients **108**, **110** and **112** are clients to server **104**. Distributed data processing system **100** may include additional servers, clients, and other devices not shown. Distributed data processing system **100** also includes printers **114**, **116** and **118**. A client, such as client **110**, may print directly to printer **114**. Clients such as client **108** and client **112** do not have directly attached printers. These clients may print to printer **116**, which is attached to server **104**, or to printer **118**, which is a network printer that does not require connection to a computer for printing documents. Client **110**, alternatively, may print to printer **116** or printer **118**, depending on the printer type and the document requirements.

In the depicted example, distributed data processing system **100** is the Internet, with network **102** representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers consisting of thousands of commercial, government, education, and other computer systems that route data and messages. Of course, distributed data processing system **100** also may be implemented as a number of different types of networks such as, for example, an intranet or a local area network.

Figure 1 is intended as an example and not as an architectural limitation for the processes of the present

invention.

With reference now to **Figure 2**, a block diagram of a data processing system in accordance with the present invention is illustrated. Data processing system **200** is an example of a hardware system console, such as hardware system console **150** depicted in **Figure 1**. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures, such as Micro Channel and ISA, may be used. Processor **202** and main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** may also include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, SCSI host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by a direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter (A/V) **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. In the depicted example, SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, CD-ROM drive **230**, and digital video disc read only memory drive (DVD-ROM) **232**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system, such as OS/2, which is available from International Business Machines Corporation. "OS/2" is a trademark of International Business Machines Corporation. An object oriented programming system, such as Java, may run in conjunction with the operating system, providing calls to the operating system from Java programs or applications executing on data processing system **200**. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on a storage device, such as hard disk drive **226**, and may be loaded into main memory **204** for execution by processor **202**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 2** may vary depending on the implementation. For example, other peripheral devices, such as optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 2**. The depicted example is not meant to imply architectural limitations with respect to the present invention. For example, the processes of the present invention may be applied to multiprocessor data processing systems.

With reference now to **Figure 3**, a block diagram of a data processing system, which may be implemented as a logically partitioned server, such as server **104** in **Figure 1**, is depicted in accordance with the present invention. Data processing system **300** may be a symmetric

multiprocessor (SMP) system including a plurality of processors **301**, **302**, **303**, and **304** connected to system bus **306**. For example, data processing system **300** may be an IBM RS/6000, a product of International Business Machines Corporation in Armonk, New York. Alternatively, a single processor system may be employed. Also connected to system bus **306** is memory controller/cache **308**, which provides an interface to a plurality of local memories **360-363**. I/O bus bridge **310** is connected to system bus **306** and provides an interface to I/O bus **312**. Memory controller/cache **308** and I/O bus bridge **310** may be integrated as depicted.

Data processing system **300** is a logically partitioned data processing system. Thus, data processing system **300** may have multiple heterogeneous operating systems (or multiple instances of a single operating system) running simultaneously. Each of these multiple operating systems may have any number of software programs executing within in it. Data processing system **300** is logically partitioned such that different I/O adapters **320-321**, **328-329**, **336-337**, and **346-347** may be assigned to different logical partitions.

Thus, for example, suppose data processing system **300** is divided into three logical partitions, P1, P2, and P3. Each of I/O adapters **320-321**, **328-329**, and **336-337**, each of processors **301-304**, and each of local memories **360-364** is assigned to one of the three partitions. For example, processor **301**, memory **360**, and I/O adapters **320**, **328**, and **329** may be assigned to logical partition P1; processors **302-303**, memory **361**, and I/O adapters **321** and

337 may be assigned to partition P2; and processor **304**, memories **362-363**, and I/O adapters **336** and **346-347** may be assigned to logical partition P3.

Each operating system executing within data processing system **300** is assigned to a different logical partition. Thus, each operating system executing within data processing system **300** may access only those I/O units that are within its logical partition. Thus, for example, one instance of the Advanced Interactive Executive (AIX) operating system may be executing within partition P1, a second instance (image) of the AIX operating system may be executing within partition P2, and a Windows 2000™ operating system may be operating within logical partition P1. Windows 2000 is a product and trademark of Microsoft Corporation of Redmond, Washington.

Peripheral component interconnect (PCI) Host bridge **314** connected to I/O bus **312** provides an interface to PCI local bus **315**. A number of Terminal Bridges **316-317** may be connected to PCI bus **315**. Typical PCI bus implementations will support four Terminal Bridges for providing expansion slots or add-in connectors. Each of Terminal Bridges **316-317** is connected to a PCI/I/O Adapter **320-321** through a PCI Bus **318-319**. Each I/O Adapter **320-321** provides an interface between data processing system **300** and input/output devices such as, for example, other network computers, which are clients to server **300**. Only a single I/O adapter **320-321** may be connected to each terminal bridge **316-317**. Each of terminal bridges **316-317** is configured to prevent the

propagation of errors up into the PCI Host Bridge **314** and into higher levels of data processing system **300**. By doing so, an error received by any of terminal bridges **316-317** is isolated from the shared buses **315** and **312** of the other I/O adapters **321**, **328-329**, and **336-337** that may be in different partitions. Therefore, an error occurring within an I/O device in one partition is not "seen" by the operating system of another partition. Thus, the integrity of the operating system in one partition is not effected by an error occurring in another logical partition. Without such isolation of errors, an error occurring within an I/O device of one partition may cause the operating systems or application programs of another partition to cease to operate or to cease to operate correctly.

Additional PCI host bridges **322**, **330**, and **340** provide interfaces for additional PCI buses **323**, **331**, and **341**. Each of additional PCI buses **323**, **331**, and **341** are connected to a plurality of terminal bridges **324-325**, **332-333**, and **342-343** which are each connected to a PCI I/O adapter **328-329**, **336-337**, and **346-347** by a PCI bus **326-327**, **334-335**, and **344-345**. Thus, additional I/O devices, such as, for example, modems or network adapters may be supported through each of PCI I/O adapters **328-329**, **336-337**, and **346-347**. In this manner, server **300** allows connections to multiple network computers. A memory mapped graphics adapter **348** and hard disk **350** may also be connected to I/O bus **312** as depicted, either directly or indirectly. Hard disk **350** may be logically partitioned between various partitions without the need

for additional hard disks. However, additional hard disks may be utilized if desired.

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 3** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

With reference now to **Figure 4**, a block diagram of an exemplary logically partitioned platform is depicted in which the present invention may be implemented. The hardware in logically partitioned platform **400** may be implemented as, for example, server **300** in **Figure 3**. Logically partitioned platform **400** includes partitioned hardware **430**, hypervisor **410**, and operating systems **402-408**. Operating systems **402-408** may be multiple copies of a single operating system or multiple heterogeneous operating systems simultaneously run on platform **400**.

Partitioned hardware **430** includes a plurality of processors **432-438**, a plurality of system memory units **440-446**, a plurality of input/output (I/O) adapters **448-462**, and a storage unit **470**. Each of the processors **432-438**, memory units **440-446**, and I/O adapters **448-462** may be assigned to one of multiple partitions within logically partitioned platform **400**, each of which corresponds to one of operating systems **402-408**.

Hypervisor **410**, implemented as firmware, creates and enforces the partitioning of logically partitioned

platform **400**. Firmware is "hard software" stored in a memory chip that holds its content without electrical power, such as, for example, read-only memory (ROM), programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), and non-volatile random access memory (non-volatile RAM).

Hypervisor **410** provides a set of firmware services to each of OS images **402-408** that safely modify the environment of each of OS images **402-408** such that interference between various ones of OS images **402-408** is prevented. Modification of the processor mode of each of processors **432-438** and address translation facilities is precluded by a hardware mode that is only deactivated when one of these hypervisor **410** services are run. Thus, the hypervisor **410** provides a small library of services that provide the richness of flexibility that hardware alone cannot provide without significantly adding to the performance overhead, since the services are firmware clones of those that the OS images would use on a standard non-partitioned platform.

To aid in understanding the present invention, consider the following example of an operating system image requesting to change an entry in a page frame table both in the context of the prior art and in the context of the present invention. A page frame table provides a translation between the logical address assigned to a system resource by an operating system image and the actual physical address of the resource within the data processing system. Each of these resources is assigned to one of OS images **402-408**. Thus, each of OS images **402-408** must be prevented from changing an entry in the

page frame table corresponding to a resource assigned to a different one of OS images **402-408**.

In the prior art firmware trapping method, the firmware protected every location within the page frame table. Every write or read instruction to one of these locations within the page frame table by an operating system image was trapped by the firmware. The firmware then decoded the instruction to determine if the location that the operating system image was attempting to write to or read from corresponded to a resource assigned to that operating system image. If the location did correspond to a resource assigned to that particular operating system image, then the instruction was executed. If the location did not correspond to a resource assigned to that particular operating system image, then the instruction was not executed. Such a procedure requires an enormous amount of overhead to analyze every one of these questionably safe instructions, most of which are safe.

In an embodiment of the present invention, the operating system images are prohibited from writing to the page frame table entirely. However, the functional equivalent of changing an entry in the page frame table is provided by hypervisor **410**. Hypervisor **410** determines, in response to a function call from one of OS images **402-408**, what the one of OS images **402-408** wishes to change, such as, for example, translating a page from its own memory to an allocated resource, and creates a separate translation table to translate the memory page to the allocated resource. Such a high level translation requires significantly less overhead than tracking every

instruction from the OS image. Each OS system image **402-408** running on logical partitioned platform **400** is modified such that rather than request to perform a questionably safe operation, the OS image **402-408** makes a request to the hypervisor **410** for the hypervisor **410** to provide the functional equivalent.

It should be noted that translating a page from memory to an allocated resource is but one example of a "questionably" safe operation. Other "questionably" safe operations to non-assignable resources may be performed by hypervisor **410** to insure that such operations are performed such that interaction with other partitions within the system is prevented.

Hypervisor **410** also may provide the OS images **402-408** running in multiple logical partitions each a virtual copy of a console and operator panel. The interface to the console is changed from an asynchronous teletype port device driver, as in the prior art, to a set of hypervisor firmware calls that emulate a port device driver. The hypervisor **410** encapsulates the data from the various OS images onto a message stream that is transferred to a computer **480**, known as a hardware system console.

Hardware system console **480** is connected directly to logically partitioned platform **400** as illustrated in **Figure 4**, or may be connected to logically partitioned platform through a network, such as, for example, network **102** in **Figure 1**. Hardware system console **480** may be, for example, a desktop or laptop computer, and may be implemented as data processing system **200** in **Figure 2**.

Hardware system console **480** decodes the message stream and displays the information from the various OS images **402-408** in separate windows, at least one per OS image. Similarly, keyboard input information from the operator is packaged by the hardware system console, sent to logically partitioned platform **400** where it is decoded and delivered to the appropriate OS image via the hypervisor **410** emulated port device driver associated with the then active window on the hardware system console **480**.

Those of ordinary skill in the art will appreciate that the hardware and software depicted in **Figure 4** may vary. For example, more or fewer processors and/or more or fewer operating system images may be used than those depicted in **Figure 4**. The depicted example is not meant to imply architectural limitations with respect to the present invention.

With reference now to **Figure 5**, a flowchart illustrating an exemplary process for preventing each of multiple OS images within a logically partitioned platform from interfering with other OS images is depicted in accordance with the present invention. The hypervisor receives a request from an operating system image to perform a potentially hazardous operation (step **502**). The hypervisor then determines if the result of the request would allow the OS direct access to platform resources outside of those allocated to its partition (step **504**). For example, the OS may wish to map an existing partition resource to a new memory address. The hypervisor knows this request is safe. If the request would not result in direct OS access to an unassigned

resource, then the hypervisor performs the OS requested function (step **506**). Continuing the example, the hypervisor then creates a translation table entry to achieve the OS image's desired result. Thus, to map the existing resource to a new memory address, the hypervisor creates a translation table entry to achieve this result. Therefore, as discussed above, a new translation table entry is created rather than allowing the OS image to change an entry or location within the page frame table itself. If, on the other hand, the OS had made a request to map a resource that was not allocated to its partition, the hypervisor would have only returned an error message (step **508**).

With reference now to **Figure 6**, a high level flowchart illustrating an exemplary process within an operating system image for requesting operations to a logically partitioned platform is depicted in accordance with the present invention. The OS image first determines that a system resource needs to be modified to accomplish a task within the OS image (step **602**). The OS image then determines whether the system resource that needs to be modified is one for which access is denied by the logically partitioned platform on which the OS image runs (step **604**). If access is not denied, then the OS image directly modifies the system resource (step **608**). If the system resource is one for which access is denied, then the OS image requests the appropriate service from the hypervisor to achieve the functionally equivalent result of the requested modification (step **606**).

It is important to note that while the present invention has been described in the context of a fully

functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media such as a floppy disc, a hard disk drive, a RAM, and CD-ROMs and transmission-type media such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.